



# TECH DATA SHEET

ProCoat Products, Inc  
 Research    Development    Manufacturing    Distribution  
 ProCoat Grid Cleaning Solution

1. **PRODUCT NAME**  
ProCoat Grid Cleaning Solution
  
2. **MANUFACTURER**  
ProCoat Products, Inc.  
260 Centre Street, Suite D  
Holbrook, MA 02343  
PH: 781-767-2270  
FAX: 781-767-2271
  
3. **PRODUCT DESCRIPTION**  
**ProCoat Grid Cleaning Solution** is a product designed specifically for treating non-porous surfaces prior to the application of **ProCoustic** Acoustical Tile & Ceiling Coating. Typical non-porous surfaces would include t-bars, air diffusers and speaker plates. When **ProCoat Grid Cleaning Solution** is applied in accordance with recommended procedures, excellent results are achieved.
  - Nicotine discoloration is removed
  - Grease and other adhesion barriers are neutralized
  - Bonding of the coating to the surface is enhanced
  - Ensures a whiter and more natural finish
  
4. **APPLICATION**  
**ProCoat Grid Cleaning Solution** is easy to apply when the following recommendations are adhered to:
  - Depending on the degree of contamination to be removed, **ProCoat Grid Cleaning Solution** may be reduced with water up to 33% (two-thirds water and one-third cleaner). A 50-50 mix is commonly used for most situations.

Using a hand or machine sprayer, moderately apply **ProCoat Grid Cleaning Solution** to the contaminated surface. Before it is allowed to dry, remove the residue from the surface using a rag or sponge. On t-bars, a sponge on a pole is most effective. Periodically rinse the rag or sponge in clean water.  
**ProCoat Grid Cleaning Solution** is intended for industrial, professional and institutional use only.

### SAFETY NOTES

**WARNING – Contains strong alkalis. Avoid contact with skin, eyes, and clothing. Rubber gloves are advised. Do not take internally. In case of contact, flush with water for at least 15 minutes and obtain medical attention. KEEP OUT OF THE REACH OF CHILDREN.**

### PRODUCT ORIENTATION

Authorized **ProCoat** Dealers and/or manufacturer representatives will provide direction with respect to:  
 Cost estimating  
 Availability for delivery  
 Product utilization

### TECHNICAL DATA

More specific information, beyond that which is provided below, can be made available upon request.  
 Water Solubility: Infinite  
 PH Concentrate: 11.8+0.5  
 Flash Point: None  
 Viscosity: 10 cps  
 Specific Gravity: 1.045  
 Cleaning Characteristics: Excellent  
 PH 1% Solution: 11.2  
 Freeze – Thaw Stability: Excellent  
 Color: Green  
 Odor: Pleasant  
 Stability: One Year Minimum

ProCoat Products, Inc  
 Research    Development    Manufacturing    Distribution  
 ProCoat Grid Cleaning Solution  
 CSI DIVISION 9